


FITTING INSTRUCTIONS FOR ECC0147 RHS CLUTCH CASE COVER MV Agusta F3 675 '12-/800 '13-/800 RIVALE '13-



In this kit there should be:

1 x Engine Case Cover (ECC0147 – with pre-fitted spacers)

3 x M6x35mm long cap head bolts

PLEASE READ THESE INSTRUCTIONS FULLY BEFORE STARTING

- Please make sure the engine is cold before proceeding with the fitting of the R&G cover.
- To fit the R&G clutch case cover remove the three T27 Torx engine case bolts in the positions arrowed above. Hold the cover loosely over the case to help identify the correct ones. DO NOT REMOVE ALL OF THE CASE BOLTS.
- Offer up the R&G cover to the engine and carefully fit it over the clutch casing. Ensure that the three R&G bolts are lined up with the holes in the engine casing, and then push on as far as it will go.
- Fit the bolts through the Engine Case Cover and into the engine case.
- With a 4mm Allen key tighten the bolts equally so that they pull the cover into place. DO NOT FULLY TIGHTEN.
- Finally use a torque wrench set at 10 nm (7 Lb ft) to fully tighten.
- It is suggested that you check the tightness of the mounting bolts on a regular basis i.e. when cleaning or once a month.



- NOTE for the cleaning of this product you should only use a soft polishing cloth and a mild general cleaning agent.
- AVOID HARMFUL CHEMICALS. IF IN DOUBT DO NOT USE AS THEY COULD ALTER THE STRENGTH OF THE COVER.
- R&G will accept no liability if the above procedure and torque settings are not followed.

ISSUE 2 27/07/2021 (DM)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.



NOTICE DE MONTAGE POUR ECC0147 PROTECTION CARTER CÔTÉ DROIT MV Agusta F3 675 '12-/800 '13-/800 RIVALE '13-

ENLEVER

ENLEVER

ENLEVER

ENLEVER

Le kit doit contenir :
eur (FCC0147 – avec ent

1 x Protection carter moteur (ECC0147 – avec entretoises pré montées) 3 x M6x35mm boulons

LIRE ATTENTIVEMENT LA NOTICE AVANT DE COMMENCER

- Veuillez vous assurer que le moteur soit froid avant de procéder au montage de la protection carter moteur R&G.
- Pour installer le couvercle du carter d'embrayage R&G, retirez les trois boulons du carter moteur Torx T27 dans les positions fléchées ci-dessus. Tenez le couvercle sans serrer sur le boîtier pour aider à identifier les bons trous. NE PAS ENLEVER TOUS LES BOULONS DU BOÎTIER.
- Présentez le couvercle R&G sur le carter moteur et ajustez-le soigneusement sur le carter. Veuillez vous assurer que les trois trous de boulons du couvercle soient alignés avec les trous du carter du moteur, puis poussez aussi loin que possible.
- Insérez les boulons à travers le couvercle du carter du moteur et dans le carter du moteur.



- À l'aide d'une clé Allen de 4mm ou d'une douille, serrez les boulons uniformément pour tirer le couvercle en place. NE PAS SERRER COMPLÈTEMENT À CE STADE.
- Enfin, utilisez une clé dynamométrique réglée à 10 N/m (7 lb/ft) pour serrer complètement.
- Il est conseillé de vérifier le serrage des boulons de fixation après le premier cycle de chauffe puis régulièrement, c'est-à-dire lors du nettoyage ou une fois par mois.
- REMARQUE: Pour le nettoyage de ce produit, vous ne devez utiliser qu'un chiffon de polissage doux et un agent de nettoyage général doux.
- ÉVITER LES PRODUITS CHIMIQUES NOCIFS. EN CAS DE DOUTE, NE PAS UTILISER CAR ILS POURRAIENT ALTRÉRER LA RÉSISTANCE DE LA PROTECTION.
- R&G n'acceptera aucune responsabilité si les procédures ci-dessus et le réglage du couple ne sont pas suivis.

ISSUE 2 27/07/2021 (DM)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.