



**Fitting Instructions for SRG0015 Radiator Guard
Kawasaki ER-6N/F '12-**



PICTURE 1



PICTURE 2

In This Kit There Should Be

- 1x Radiator Guard**
- 2x 100mm Lengths of Foam**
- 2x Spacers 19 mm long**
- 3x M6 Dome nuts**
- 2x M6x35mm long button head bolts**
- 1x M6x16mm long button head bolts**

FTTING INSTRUCTIONS

- To fit the radiator guard to the bike cut the foam strip provided into 10mm wide pieces and stick them to the back of the radiator guard frame, so that they sit between the radiator guard and the radiator.
- Remove the two upper radiator mounting bolts in position (you will need to remove the original bolt from the rear of the radiator).
- Remove the lower mounting bolt from the right-hand side (as you sit on bike) in position shown in picture 1 (you will need to remove the original bolt from the rear of the radiator).

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



- Replace the two upper radiator mounting bolts with the M6x35, fit these bolts from the back of radiator; this will leave approximately 28mm of thread protruding and tighten.
- Place the two spacers over the exposed threads on the upper mounting bolts.
- Offer up the radiator guard to the radiator, ensuring the logo sits at the bottom. The upper mounting brackets should fit over the exposed threads.
- Replace the lower mounting bolt with the M6x16 as original; this will leave approximately 10mm of thread protruding and tighten.
- Fit the three M6 dome head nuts and secure the radiator guard.

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

Issue 1 23/09/2013 (AR)



**Montageanleitung für den SRG0015 Kühlerschutz
Kawasaki ER-6N/F '12-**



ABBILDUNG 1



ABBILDUNG 2

Dieser Kit enthält:

- 1x Kühlerschutz**
- 2x 100mm Schaumstoffstreifen**
- 2x Abstandhalter 19 mm Länge**
- 3 x M6 Hutmutter**
- 2x M6x35mm Halbrundkopfschraube**
- 1x M6x16mm Halbrundkopfschraube**



MONTAGEANLEITUNG

- Um den Kühlerschutz am Motorrad zu montieren, schneiden Sie zuerst die mitgelieferten Schaumstoffstreifen in 10 mm breite Streifen und kleben Sie diese auf der Rückseite des Kühlerschutzrahmens, so dass sie zwischen dem Kühlerschutz und dem Kühler angebracht sind
- Entfernen Sie die zwei Montageschrauben für den Kühler oben (hierbei müssen Sie die Originalschraube hinten am Kühler entfernen).
- Entfernen Sie die untere Montageschraube auf der rechten Seite (in Fahrtrichtung) des Kühlerschutzes wie in Abbildung 1 abgebildet (Sie werden die Originalschraube hinten am Kühler entfernen müssen).
- Ersetzen Sie die zwei oberen Montageschrauben mit den M6x35mm Halbrundkopfschrauben. Montieren Sie diese Schrauben am Kühler hinten – ca. 28mm Gewinde wird hervorstehen – und befestigen.
- Die Abstandshalter an den hervorstehenden Gewinden der oberen Montageschrauben anbringen.
- Den Kühlerschutz an den Kühler ansetzen – das Logo ist unten. Die oberen Montagehalterungen an den hervorstehenden Gewinden anbringen.
- Ersetzen Sie die untere Montageschraube mit der M6x16mm Halbrundkopfschraube – ca. 10mm Gewinde wird hervorstehen – und befestigen.
- Montieren Sie die drei M6 Hutmutter und befestigen Sie den Kühlerschutz.

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

Ausgabe 1 23/09/2013 (AR)



INSTRUCTIONS DE MONTAGE POUR SRG0015 Grille de protection radiateur
Kawasaki ER-6N/F '12-



PHOTO 1



PHOTO 2

Le kit doit contenir :

- 1x Grille de protection radiateur**
- 2x 100mm Mousse autocollante**
- 2x Entretoises 19 mm de long**
- 3x M6 Ecrous**
- 2x M6x35mm Boulons**
- 1x M6x16mm Boulons**



INSTRUCTIONS DE MONTAGE :

- Couper la mousse autocollante en bandeaux de 10mm de large et collez les au bas du cadre de support protection radiateur, de façon à ce qu'ils se retrouvent entre la grille de protection et le radiateur.
- Enlever les 2 boulons supérieurs de fixation du radiateur en position (Vous devrez retirer le boulon d'origine de l'arrière du radiateur).
- Enlever le boulon de fixation inférieur du côté droit (assis sur la moto) en position indiquée sur la photo 1 (Vous devrez retirer le boulon d'origine de l'arrière du radiateur).
- Remplacer les 2 boulons de fixation supérieurs par les boulons M6x35, passer ces boulons par le bas du radiateur, cela laissera approximativement 28mm de filetage dépasser puis serrer.
- Placer les 2 entretoises sur les filetages exposés des boulons supérieurs de fixation.
- Monter la grille de protection radiateur sur le radiateur, en veillant à ce que le logo soit au bas. Les supports de fixation supérieurs doivent se placer autour des filetages exposés.
- Remplacer le boulon de fixation inférieur par le M6x16 comme à l'origine. Cela laissera environ 10mm de filetage dépasser, puis serrer.
- Monter les 3 écrous M6 puis fixer la grille de protection.

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

Issue 1 23/09/2013 (AR)