



Fitting Instructions for SRG0019 Radiator Guard
SUZUKI BANDIT GSF1250S & N '07-



In This Kit There Should Be
1x Radiator Guard (SRG0019)
1x M6x 25mm Long Button Head Bolt
2x M6x 35mm Long Button Head Bolts
3x M6 Washers
2x 100mm Lengths of self-adhesive Foam



Picture 1



Picture 2



Picture 3



Picture 4

TOOLS REQUIRED

- Socket set to include 4mm A/F & 10mm socket & wrench.

FITTING INSTRUCTIONS

- To fit the radiator guard to the bike cut the foam strip provided into 10mm wide pieces and stick them to the back of the radiator guard frame, so that they sit between the radiator guard and the radiator.
- Remove the bolt that secures the bottom of the radiator in place, as shown in picture 1.
- Remove the two bolts that secure the two top mounts of the radiator in place, as shown in picture 2.
- Offer the R&G Radiator Guard into place on the bike, ensuring that the brackets on the top of the radiator guard located on the rubber mounts at the top of the radiator, before fitting the two M6 x 35mm long button head bolts provided with washers on through the radiator guard and into the frame mounts, as shown in picture 3.
- On the bottom mount, locate the remaining M6 x 25mm long button head bolt through the remaining washer, then through the lower mount of the radiator guard and into the threaded radiator boss, before tightening, as shown in picture 4.
- Ensure the radiator guard is correctly mounted and tighten all bolts evenly.

ISSUE 1 07/10/2013 (AR)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



Montageanleitung für den SRG0019 Kühlerschutz
SUZUKI BANDIT GSF1250S & N '07-



Dieser Kit enthält
1x Kühlerschutz (SRG0019)
1x M6x 25mm Halbrundkopfschraube
2x M6x 35mm Halbrundkopfschrauben
3x M6 Unterlegscheiben
2x 100mm selbstklebende Schaumstoffstreifen



Abbildung 1



Abbildung 2



Abbildung 3



Abbildung 4

SIE BENÖTIGEN FOLGENDES WERKZEUG.

- Steckschlüssel-Satz inkl. 4mm & 10mm Steckschlüssel

MONTAGEANLEITUNG

- Um den Kühlerschutz am Motorrad zu montieren, schneiden Sie zuerst die mitgelieferten Schaumstoff-Streifen in 10 mm breite Streifen und kleben Sie diese auf der Rückseite des Kühlerschutzrahmens, so dass sie zwischen dem Kühlerschutz und dem Kühler angebracht sind.
- Entfernen Sie die Schraube, die den Kühler unten befestigt – siehe Abbildung 1.
- Entfernen Sie die zwei Schrauben, die die zwei oberen Kühlerhalterungen befestigen – siehe Abbildung 2.
- Den R&G Kühlerschutz in Position bringen – achten Sie hierbei darauf, dass die Halterungen oben am Kühlerschutz an den Gummihalterungen oben am Kühler sind, bevor Sie die zwei M6 x 35mm Halbrundkopfschrauben mit Unterlegscheiben durch den Kühlerschutz in die Rahmenhalterungen eindrehen – siehe Abbildung 3.
- Die M6 x 25mm Halbrundkopfschraube durch die übrige Unterlegscheibe schieben, dann durch die untere Kühlerschutzhalterung in die Gewinde-Lochplatte einführen – siehe Abbildung 4.
- Überprüfen Sie, dass der Kühlerschutz ordnungsgemäß angebracht ist und ziehen Sie alle Schrauben gleichmäßig fest.

AUSGABE 1 07/10/2013 (AR)



INSTRUCTIONS DE MONTAGE POUR SRG0019 Grille de protection radiateur
SUZUKI BANDIT GSF1250S & N '07-



Le kit doit contenir :

- 1x Grille de protection radiateur (SRG0019)
- 1x M6x 25mm Boulon
- 2x M6x 35mm Boulons
- 3x M6 Rondelles
- 2x 100mm Mousse autocollante



R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



Photo 1



Photo 3

Photo 2



Photo 4

Outils requis

- Jeu de clés à douille 4mm & 10mm

INSTRUCTIONS DE MONTAGE:

- Couper la mousse autocollante en bandeaux de 10mm de large et collez-les au bas du cadre de support protection radiateur, de façon à ce qu'ils se retrouvent entre la grille de protection et le radiateur.
- Enlever le boulon qui fixe le bas du radiateur en place (photo 1).
- Prendre les 2 boulons qui fixent les 2 supports supérieurs du radiateur en place (photo 2).
- Mettre la grille de protection en place sur la moto, en veillant à ce que les supports sur le haut de la grille de protection radiateur placés sur les supports en caoutchouc sur le haut du radiateur, avant d'insérer les 2 boulons M6 x 35mm fournis avec rondelles à travers la grille de protection radiateur et dans les supports de cadre (photo 3).
- Sur le support du bas, placer le boulon M6 x 25mm restant à travers la rondelle restante, puis à travers le support inférieur de la grille de protection radiateur et dans le patron fileté du radiateur, avant de serrer (photo 4).
- Veiller à ce que la grille de protection soit correctement montée puis serrer tous les boulons de façon égale.

ISSUE 1 07/10/2013 (AR)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.