

## **FITTING INSTRUCTIONS FOR RAD0346PRO**



THIS KIT CONTAINS THE ITEMS PICTURED AND LABELLED OVER PAGE.

SOME PARTS MAY BE SHOWN FOR CLARITY OF INSTRUCTIONS ONLY.

DO NOT PROCEED UNTIL YOU ARE SURE ALL PARTS ARE PRESENT.

#### PLEASE READ ALL INSTRUCTIONS BEFORE PROCEEDING.

# IF IN ANY DOUBT WHEN FITTING OUR PRODUCTS, CONSULT ONE OF OUR DEALERS OR HAVE FITTED BY A QUALIFIED TECHNICIAN.

PLEASE NOTE THAT THE WAY THE KIT IS PACKED DOES NOT NECESSARILY REPRESENT THE WAY OF MOUNTING TO THE BIKE.

IN THE EVENT OF RUBBER WASHERS BEING USED TO HOLD COMPONENTS ONTO BOLTS,

THESE RUBBER WASHERS CAN BE THROWN AWAY.

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 <a href="www.rg-racing.com">www.rg-racing.com</a> Email: <a href="mailto:info@rg-racing.com">info@rg-racing.com</a>



### **TOOLS REQUIRED**

SET OF ALLEN KEYS

• WIRE CUTTERS

### **GENERAL TORQUE SETTINGS**

M4 BOLT = 8Nm

M5 BOLT = 12Nm

M6 BOLT = 15Nm

M8 BOLT = 20Nm

M10 BOLT = 40Nm

M12 BOLT = 40Nm

## **LEGEND**

ITEM NO.	DESCRIPTION	QTY
ITEM 1	RAD0346PRO RADIATOR GUARD	1
ITEM 2	CABLE TIES	5
ITEM 3	RUBBER BUNG	6
ITEM 4	BUTTON HEAD BOLTS	2
ITEM 5	WASHERS	2

## **FITTING DIAGRAM**

FRONT OF RAD GUARD




Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 <a href="www.rg-racing.com">www.rg-racing.com</a> Email: <a href="mailto:info@rg-racing.com">info@rg-racing.com</a>


Page **3** of **4** RAD0346PRO



**FITTING PICTURES** 



Picture 2





## FITTING INSTRUCTIONS

- Firstly, remove any existing radiator guard and carefully clean the radiator, being careful not to damage any of the fins.
- To fit R&G radiator guard to the bike, insert the 3x rubber grommets into the radiator guard in the holes circled in green in the **Picture 1** above.
- Offer the radiator guard up to the bike and pass the button head bolt with washer through the top
  hole in the radiator guard (heat resistant thread locking compound should be applied to the bolt) and
  into the threaded hole in the radiator, only tightening by a few threads to keep the radiator guard
  loose until the other fixings are in place.

#### See Picture 2

- Then loosely thread the remaining bolt and washer in the lower mounting hole.
- Once loosely fitted, pass the cable tie through the radiator guard and around the radiator bracket located between the two cable tie slots.
- Tighten both bolts fully, then tighten the cable tie and trim the excess.

ISSUE 1 - 05/06/2024 (TB)

#### **CONSUMER NOTICE**

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

#### **R&G RACING RETURNS POLICY (NON-FAULTY GOODS)**

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 <a href="www.rg-racing.com">www.rg-racing.com</a> Email: <a href="mailto:info@rg-racing.com">info@rg-racing.com</a>